



Remote Browser Isolation

22.07

On-Premises Deployment Guide

© 2022 Forcepoint

Forcepoint and the FORCEPOINT logo are trademarks of Forcepoint.
All other trademarks used in this document are the property of their respective owners.

Published 17 August 2022

Every effort has been made to ensure the accuracy of this document. However, Forcepoint makes no warranties with respect to this documentation and disclaims any implied warranties of merchantability and fitness for a particular purpose. Forcepoint shall not be liable for any error or for incidental or consequential damages in connection with the furnishing, performance, or use of this manual or the examples herein. The information in this documentation is subject to change without notice.

Contents

1 Introduction	5
Deployment prerequisites.....	5
Network communication requirements.....	6
2 Deploying Forcepoint RBI	9
Deploy Forcepoint RBI.....	10
3 Post-deployment steps	21
Cipher implementation.....	21
Configure SMTP.....	22

Chapter 1

Introduction

Contents

- [Deployment prerequisites](#) on page 5
- [Network communication requirements](#) on page 6

Forcepoint Remote Browser Isolation (Forcepoint RBI) helps organizations experience a safer internet by proactively stopping web, email, and document-based threats. This document captures the prerequisites for an on-premises deployment of Forcepoint RBI. Details have been provided for recommended network port openings required for communication.

Forcepoint RBI has three major components:

- **Control Center Cluster (Master & Worker):** The Control Center cluster contains the Forcepoint RBI Admin Portal and Superadmin Portal. The Portal is responsible for policy management, user authentication, logging, dashboard, and reporting.
- **RBC Cluster (Master & Worker):** The Remote Browsing Containers (RBCs) house the remote browsers that connect to the Internet to fetch, execute, and render the content.
- **Proxy:** The proxy handles all traffic redirection from the end user's browser to the RBC.

This document provides the specifications required for the Virtual Machine and Network Communication. Refer to the *Sizing Guide* for hardware specifications for Forcepoint RBI.

Deployment prerequisites

Before deploying Forcepoint RBI in an on-premises environment, review these prerequisites.

- Virtualization platform should be based on any of the following virtualization products:
 - Virt-Manager (KVM)
 - Oracle VirtualBox
 - VMware
- Forcepoint RBI systems should be reachable from endpoint machines (end user systems).
- One IP address is to be assigned to each Forcepoint RBI component (master, worker, proxy).
- Public Wildcard SSL certificate or a Self-Signed SAN-based wild card certificate, including RBI servers IP address as SAN, is required for Forcepoint RBI. Public certificate, Private key, and CA certificates are required.
For Self-Signed certificates, install the Root CA Chain Certificate on the endpoint machines under **Trusted Root CA Authority**.
- The FQDN names of Forcepoint RBI should be resolved by the endpoint machines by following one of these options:
 - Add DNS entries for Forcepoint RBI FQDNs and URLs to the respective domain.
 - Add the FQDN entries for Forcepoint RBI in the user's endpoint machine host file (`C:\windows\system32\drivers\etc\hosts`). This requires Admin access to the endpoint machine.

- If there is a local/Internal DNS in place for resolving Intranet/Internal servers and it is configured as a DNS server in the user's endpoint machine, then create a zone for the domain of the FQDN in the Local/Internal DNS and add the host entries to it so that users can resolve the FQDNs through local/Internal DNS.
- The Forcepoint RBI instances need to be provided with DNS servers that can resolve Global domains.
- If a proxy server is in place, then the IP address and the port of the proxy server must be configured in Forcepoint RBI.
- Internet connectivity is required for setting up Forcepoint RBI and for browsing through Forcepoint RBI.
- For final deployment, the actual resource requirements are calculated based on the *Sizing Guide* and on the following:
 - User concurrency
 - Internet usage pattern
- The hardware specification requirement for production deployment will be in accordance with the *Sizing Guide*. Check the *Sizing Guide* details with your administrator or a Forcepoint representative for details on the resources required and number of VMs required for installing and configuring the Forcepoint RBI. The resource requirements are calculated based on the following:
 - User concurrency
 - Internet usage pattern
- The wildcard entry of the Forcepoint RBI base domain is to be bypassed (set exception) in the end user proxy settings.
- According to the *Sizing Guide*, RBI consists of the following components:

Admin Portal	RBC Cluster	RBI Proxy**
Master	Master	Proxy
Worker	Worker-RBC	
	Worker-File Scanning	
	Worker-Control Plane	

** RBI Proxy is applicable only in case of Proxy chaining.

- The Master and Worker for the respective cluster (Control Center and RBC) should be hosted in the same LAN segment. The Master and Workers should have no protocol or port restrictions.

Network communication requirements

Forcepoint RBI communicates with the endpoint using WebSocket on custom ports. This section shows the ports that needs to be opened for communication with Forcepoint RBI.

Connection	Required ports
Endpoint machine to Forcepoint RBI Control Center Cluster	tcp 443 (Session initialization)
Endpoint machine to Forcepoint RBI RBC Cluster (including all RBC worker nodes).	tcp 443 (Session initialization) tcp 30000 – 32767 (Secure WebSocket connection (WSS) for Remote Browsing container)

Connection	Required ports
Forcepoint RBI Cluster Communication (Control Center Cluster to RBC Cluster)	tcp 443 (RBI cluster communication)
Internet access to Forcepoint RBI Cluster (RBC Cluster to Internet)	tcp 443 (Internet access to RBC Cluster) tcp "Proxy IP & Proxy Port" (Proxy IP and Proxy port in case Internet access is provisioned through Enterprise Proxy.)
Terminal access (Admin user to Forcepoint RBI instances)	tcp 2200
Forcepoint Web Security Gateway/Proxy settings	Add base domain wildcard (e.g., *.rbi.forcepoint.com) to bypass list in end user Proxy settings.
CDR Service: API call to CDR service from Forcepoint RBI	tcp 80, 443 (destination *.threat-removal.deep-secure.com)
FTIS Service: API call to FTIS service from Forcepoint RBI	tcp 80, 443 (destination *. cloud.threatseeker.com)
Endpoint machine to LB (Admin and RBC)	443
Admin Portal LB to RBC LB	443
LB (Admin and RBC) to Masters	443

Chapter 2

Deploying Forcepoint RBI

Contents

- Deploy Forcepoint RBI on page 10

This chapter provides the instructions for deploying Forcepoint RBI in an on-premises environment.



Note

- Read the *Sizing Guide* for the hardware resources required for each VM component before beginning the deployment.
- The VMs and resources are to be provisioned based on the sizing exercise conducted to determine the total number of hardware resources (vCPU, Memory, Disk) needed. The *Sizing Guide* provides the total number of resources required as well resources required for each RBI component.
 - The maximum vCPU per VM/Physical server for Worker (for both Core and RBC) should be 64 vCPU.
 - The minimum vCPU per VM/Physical server for Worker (for both Core and RBC) should be 32 vCPU.

Based on a sample sizing, here is an illustration of the number of virtual machines required for each component:

	Admin Portal		RBC Cluster				RBI Proxy**	Final Total
	Master	Worker	Master	Worker-RBC*	Worker-File Scanning*	Worker-Control Plane*	Proxy	
vCPUs	20	36	20	1024	36	20	24	1180
Memory	80	144	80	4096	144	80	96	4720
Storage SSD (in GB)	40	180	40	1280			40	1580
DB Storage SSD (in GB)								
No.of Vms (64 vCPU each VM)	1 vm/20 vCPUs	1 vm/36 vCPUs	1 vm/20 vCPUs	16 vms/64 vCPU each	1 vm/36 vCPUs	1 vm/20 vCPUs	1 vm/24 vCPUs	
No.of Vms (32 vCPU each VM)	1 vm/20 vCPUs	1 vm/36 vCPUs	1 vm/20 vCPUs	32 vms/32 vCPU each	1 vm/36 vCPUs	1 vm/20 vCPUs	1 vm/24 vCPUs	

*During the RBI setup, add RBC Cluster File Scanning and Control Plane Workers along with RBC cluster Worker section in the `cluster.yaml` file and note the IP address of the RBC Cluster File Scanning and Control Plane nodes. Nodes' labels are changed post-installation.

** RBI Proxy is applicable only in case of Proxy chaining, not applicable for URL based redirection.

- Provision the number of VMs accordingly after reading the RBI sizing guide and conducting the RBI sizing exercise.
- After all of the VMs are configured with IP addresses, proceed with the RBI setup.

Deploy Forcepoint RBI

This topic provides the procedure for deploying Forcepoint RBI in on-premises environments. Before deploying Forcepoint RBI, obtain the ISO from Forcepoint.

Steps

- 1) Install and deploy the Forcepoint RBI ISO obtained from Forcepoint.
- 2) Each Forcepoint RBI instance/VM is to be setup using the same ISO.
- 3) After the VM is ready, SSH to the VM using port 2200 with the login credentials (Username: maint Password: admin), and assign the static IP address to the VM.



Note

Keep a copy of the IP address, Netmask, Gateway, and DNS details. You will need these details later.

- 4) Set the IP addresses and network details:
 - a) Open a command prompt or terminal and run the following two commands:

```
# cd scripts
# sudo ./setip.sh
```

```
maint@prod-kubemaster-1:~$ cd scripts
maint@prod-kubemaster-1:~/scripts$ sudo su
root@prod-kubemaster-1:/home/maint/scripts# ./setip.sh
```

- b) Select **interface 1** or the serial number against the interface name connected to the virtual network, then press **Enter**.
- c) For **Do you want to use DHCP for this interface (y/n)**, type **n**, then press **Enter**. (Please set the static IP address)
- d) Enter the **IP Address** (for example, **192.168.2.201**), then press **Enter**. (Please select your IP address)
- e) Enter the **Subnet mask** (for example, **255.255.255.0**), then press **Enter**. (Please select your subnet mask)
- f) Enter the **Gateway** (for example, **192.168.2.1**), then press **Enter**. (Please select your gateway)

- g) Enter the **DNS IP** (for example, **8.8.8.8**), then press **Enter**. If you are entering multiple DNS IP addresses, separate the IP addresses with commas. (Please select your DNS)
- h) Repeat these steps on all required VMs.

- 5) Verify the IP address with the following command:

```
ip a
```

```
2: ens33: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast state UP group default qlen 1000
    link/ether 00:0c:29:b9:ea:d8 brd ff:ff:ff:ff:ff:ff
    inet 192.168.2.201/24 brd 192.168.2.255 scope global ens33
        valid_lft forever preferred_lft forever
    inet6 fd15:4ba5:5a2b:1002:20c:29ff:feb9:ead8/64 scope global tentative mngtmpaddr dynamic
        valid_lft 86400sec preferred_lft 14400sec
    inet6 fe80::20c:29ff:feb9:ead8/64 scope link
        valid_lft forever preferred_lft forever
```

- 6) Shut down the VM, then start the VM again.

```
sudo shutdown -h now
```




Note

- Make sure all the VMs required for the RBI components are created before you proceed with RBI setup and installation.
- Note down the IP address of all the VMs in a spread sheet.
- To relate the VMs to the RBI components, tag the respective VMs against the respective RBI component.
- Use one of the primary VMs from the RBI Admin portal Master component to download the RBI deb package and run the setup.
- Before running the RBI setup, make sure all the VMs are powered ON and reachable via port 2200.

- 7) SSH to the primary VM (Admin Portal Master VM) using port 2200 with the login credentials (Username:maint Password: admin).

- 8) Using WinSCP or scp, copy the unarchived infra directory to Core master - `/home/maint` provided by Forcepoint.

For Windows:



For Mac/Linux:

- To untar the tar file:

```
tar xf infra.tar
```

- To copy the untar file to Core master IP:

```
scp -r -P 2200 infra/ maint@<core_master_ip>:~/.
```

- 9) Update `/home/maint/infra/islasetaup/cluster.yaml` with the following required details:

```
nano /home/maint/infra/islasetaup/cluster.yaml
```


- a) Add the client certificates.

```
kubernetes:
  certs:
    publickey: keys/fp.dev.crt
    privatekey: keys/fp.dev-domain.key
    ca: keys/fp.dev-CA.crt
```



Note

Use WinSCP or the `scp` command to copy the required certificate and key to `/home/maint/infra/islasetaup/keys`.



- b) Add the Core master node 1 IP address (Admin Portal Master VM IP address):

```
loadbalancer:
  ip: ""
  baseurl: .fp.dev
  cluster:
    core:
      masters:
        - node: 1
          ip: 192.168.122.231
          sshport: 2200
          sshuser: maint
          reset: 0
```



Note

For Single cluster Multi master setup (Core master IPs = RBC master IPs),

Prerequisites:

- We recommend that you use your own Load Balancer. If you are using the RBI Load Balancer, then follow the below steps:

- i) Go to script placed in `/home/maint/infra/islasetup/helperscripts/archive/loadbalancer.sh`
- ii) Run it on the server you want to configure as the Load Balancer in below format:

```
./loadbalancer.sh lbip, master1_ip, master2_ip, master3_ip
```

- Three Master VM Nodes are required
Perform the below steps in `cluster.yaml`

- i) Add the Load Balancer IP in `cluster.yaml`.

```
loadbalancer:
  ip: "192.168.122.100"
```

- ii) Add two more Master node entries.

```
core:
  masters:
    - node: 1
      ip: 192.168.122.41
      sshport: 2200
      sshuser: maint
      reset: 1
    - node: 2
      ip: 192.168.122.42
      sshport: 2200
      sshuser: maint
      reset: 1
    - node: 3
      ip: 192.168.122.43
      sshport: 2200
      sshuser: maint
      reset: 1
```

- c) Add the Core worker node 1 IP address (Admin Portal Worker VM IP address):

```
workers:
- node: 1
  ip: 192.168.122.231
  sshport: 2200
  sshuser: maint
  reset: 0
```

If there are multiple workers, add entries for each worker (for example, from node to reset for each worker).

```
workers:
- node: 1
  ip: 192.168.122.166
  sshport: 2200
  sshuser: maint
  reset: 1
- node: 2
  ip: 192.168.122.213
  sshport: 2200
  sshuser: maint
  reset: 1
```

- d) Add the RBC master node 1 IP address (RBC Cluster Master VM IP address):

```
rbc:
  masters:
- node: 1
  ip: 192.168.122.231
  sshport: 2200
  sshuser: maint
  reset: 0
```



Note

In case of Single cluster Multi master setup (Core master IP Addresses = RBC masters' IP Addresses), add 2 more master entries under RBC cluster.

```
rbc:
  masters:
- node: 1
  ip: 192.168.122.41
  sshport: 2200
  sshuser: maint
  reset: 0
- node: 2
  ip: 192.168.122.42
  sshport: 2200
  sshuser: maint
  reset: 0
- node: 3
  ip: 192.168.122.43
  sshport: 2200
  sshuser: maint
  reset: 0
```

- e) Add the RBC worker node 1 IP address (RBC Cluster Worker VM IP address):

```
workers:  
- node: 1  
  ip: 192.168.122.231  
  sshport: 2200  
  sshuser: maint  
  reset: 0
```

If there are multiple workers, add entries for each worker (for example, from node to reset for each worker).

```
workers:  
- node: 1  
  ip: 192.168.122.240  
  sshport: 2200  
  sshuser: maint  
  reset: 1  
- node: 2  
  ip: 192.168.122.128  
  sshport: 2200  
  sshuser: maint  
  reset: 1
```



Note

- During the RBI setup, add RBC Cluster File Scanning and Control Plane Workers along with RBC cluster Worker section in the `cluster.yaml` file and note the IP address of the RBC Cluster File Scanning and Control Plane nodes. Nodes' labels are changed post-installation.
- If the Core and RBC workers IP addresses different for Single cluster Multi Master deployment, then add the RBC workers IP addresses in the Core Worker section.

f) Add cluster information. For example:

```
data:
  core:
    valuepath: values-on-prem.yaml ( File which needs to be used for
helm core installation)
    releasename: core (Name of the release for core)
    version: default with the version that needs to be deployed
    pvtype: nfs
    reset: 0
  rbc:
    location: 1 ( Based on the region. USA = 1, UK = 2)
valuepath: values-on-prem.yaml ( File which needs to be used for helm rbc installation)
    releasename: rbc (Name of the release for rbc)
    version: default with the version that needs to be deployed
    pvtype: nfs
    reset: 0
```

```
helm:
  cluster:
    core:
      valuepath: values-core.yaml
      releasename: core
      version: 2022.07.65
      pvtype: nfs
      reset: 0
    rbc:
      location: 1
      valuepath: values-rbc.yaml
      releasename: rbc
      version: 2022.07.28
      pvtype: nfs
      reset: 1
```

**Note**

If the Core Master and RBC Master IP addresses are the same, then select **values-core-single.yaml** instead of **values-core.yaml** for core and select **values-rbc-single.yaml** instead of **values-rbc.yaml** for RBC.

g) Add database password (Default password is test123# encoded to base64).

```
database:
  dbuser: isla
  dbpass: dGVzdDEyMyMK
```

h) Add superadmin details under the data tag. For example:

```
data:
  superadmin:
    name: rbiadmin (This will become the superadmin url e.g. https://
rbiadmin.secureinc.org
    email: admin@secureinc.org (Administrators email address)
    password: Default password is "Welcome123#" encoded to base64.
```

```
data:
  superadmin:
    name: rbiadmin
    email: admin@secureinc.org
    password: V2VsY29tZTEyMyMK
```


i) Add tenant details under the data tag. For example:

```
tenants:
  host: rbi (This will become the tenant url e.g. https://rbi.secureinc.org
  squidport: squidport is to be defined only if RBI is to be deployed in a
              proxy chaining mode(as a parent proxy or upstreaming proxy to
              Customer's existing proxy). For example, if you want to host
              the RBI proxy on port 3134 then define 3134 against squidport.
              Squid certificate needs to be installed on the customers
              existing proxy(child proxy). Certificate can be found at
              /home/maint/infra/islaproxy and file is squid-ca-cert-key.pem
              Note: If you already have RBI deployed without RBI proxy and
              want to deploy RBI proxy component only post RBI deployment
              then edit the cluster.yaml file in the infra/islasetup directory,
              specify the squid port, save the cluster.yaml file and then
              run ./squid.sh cluster.yaml. This will install RBI proxy component.
              Once the RBI proxy component is installed, the RBI proxy is
              accessible on Core Clusters Master IP and the specified squidport
              for example: 192.168.122.41:3134 (if the squidport specified as
              3134 in cluster.yaml).
  icapport: for icap the default port is set to 1344. It is recommended not
              to change the icap port unless you want to Integrate RBI with your
              existing On-premises proxy with icap/icaps. To integrate RBI with
              existing On-premises Proxy for icap/icaps based integration, ensure
              that your existing proxy supports icap/icaps. To integrate with
              icaps, define port 11344 in the cluster.yaml configuration, also
              ensure to obtain the RBI ICAP Integration guide to configure your
              On-premises proxy for icap/icaps based integration for RBI.
  email: admin@rbiinc.org (Administrators email address)
  password: Default password is "Welcome123#" encoded to base64.
```

```
tenants:
- host: rbi-tenant-hb
  name: Rbi-tenant-hb
  squidport: 3130
  icapport: 1344 ##1344 or 11344
  admin:
    name: Rbi-tenant
    email: admin@rbi-tenant.org
    password: V2VsY29tZTEyMyMK
```

**Note**

Based on the selection for squidport and icapport, have the port open accordingly.

j) Add the tenant hostname in appliance-rbi:

```
appliances:
- name: appliance-rbi
  tenanhost: rbi
  minnodes: 2
  maxnodes: 2
  racversion: ract-direct:r89-5.5.11
  racurl: https://rbc-cluster-down.fp.dev
```

- k) Add the **rac-url** (RBI server url) in **appliances-racurl**. Also, based on the license, modify the **minnodes** and **maxnodes**. For example, if the license is for 1,000 sessions, then minnodes can be 100 and maxnodes can be 1000.

```
minnodes: 2
maxnodes: 2
racversion: ract-direct:beta-92-6.0.3
racurl: rbc-cluster-gg.fp.dev
```

- 10) Run the **islasetup** from `/home/maint/infra/islasetup`.

```
./islasetup cluster.yaml
```



Note

- If the Core and RBC workers IP addresses different for Single cluster Multi Master deployment, then run the below commands:

- a) Run `kubectl get nodes` and get the name against the worker(s).

```
maint@core-kubemaster-1:~$ kubectl get nodes
NAME                STATUS    ROLES    AGE   VERSION
core-kubemaster-1   Ready    control-plane,master   19h   v1.20.4
core-kubeworker-1   Ready    <none>    19h   v1.20.4
```

- b) The workers that needs to function for Core cluster make rbc labels false for the Core worker(s).

```
kubectl label nodes <core-kubeworker-#> isla/rbc-document-handler-node-
isla/document-handling-node- isla/rbc-node-
```


- c) The workers that needs to function for RBC cluster make core labels false for the RBC worker(s).

```
kubectl label nodes <core-kubeworker-#> isla/rbc-core-services- isla/cc-
core-services-
```

- 11) Add the required host file entries in end user system if DNS is not added to the public domain. For example:


```
Core Master ip rbiadmin.secureinc.org rbi.secureinc.org
RBC Master ip rbi-cluster.secureinc.org
RBC Worker1 ip(say x.x.x.x) rbchost-x-x-x-x.secureinc.org
RBC Worker2 ip(say y.y.y.y) rbchost-y-y-y-y.secureinc.org
```

- 12) After the installation, sign in to the Forcepoint RBI superadmin portal and select **Auto Provision** under **Settings > Appliances**.



- 13) Login to **Admin Portal > Accept the EULA > Enter license key** obtained from Forcepoint operations team.

- 14) For anonymous browsing, the URL will be `https://<replace_With_tenant_url>/viewer/loader?tenantId=<replace_with_tenantid>&username=<replace_with_username>url=<replace_with_site_navigate>`. The Tenant ID can be found in the Forcepoint RBI Admin Portal.



Contents

- Cipher implementation on page 21
- Configure SMTP on page 22

As part of the post-deployment steps, this chapter discusses cipher implementation, and configuring SMTP.

Cipher implementation

This topic provides the procedure for implementing the Forcepoint-approved ciphers.

Steps

- 1) SSH to the Core Master and edit kubelet config.yaml:

```
sudo vim /var/lib/kubelet/config.yaml
```

- 2) Add the following content to the end of the file:

```
tlsCipherSuites: [TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,  
TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,  
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,  
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384]
```

```
streamingConnectionIdleTimeout: 0s  
syncFrequency: 0s  
volumeStatsAggPeriod: 0s  
tlsCipherSuites: [TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_EC  
DHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384]
```

- 3) Restart kubelet.service:

```
sudo systemctl restart kubelet.service
```

- 4) Edit kube-apiserver.yaml:

```
sudo vim /etc/kubernetes/manifests/kube-apiserver.yaml
```

- 5) Add the following content at the end of the **Command** section:

```
- --tls-cipher-suites=TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,
  TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,
  TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,
  TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
```

```
tls-private-key:/etc/kubernetes/pki/apiclient-key
- --tls-cipher-suites=TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
image: k8s.gcr.io/kube-apiserver:v1.20.13
imagePullPolicy: IfNotPresent
```

- 6) Check that the nodes are up:

```
kubectl get node
```


- 7) Repeat these cipher implementation steps for all Masters.

Configure SMTP


Simple Mail Transfer Protocol (SMTP) configuration enables email notifications to administrators through the Forcepoint RBI Portal.

Steps

- 1) Sign in to the Forcepoint RBI superadmin portal and go to **Organizations**.
- 2) Click the globe icon to open Global Settings.



- 3) In **Global Settings**, enter the SMTP configuration shown in the following image:



The screenshot shows the Forcepoint Global Settings page. The left sidebar contains navigation options: Dashboard, System, Administration (Users, Organizations), and Settings (Appliances). The main content area is titled 'Notification Settings' and contains an 'SMTP Configuration' section. The configuration fields are as follows:

Field	Value
SMTP Hostname	smtp.gmail.com
Require Authentication	<input checked="" type="checkbox"/>
Username	testingthetestqa@gmail.com
Password	*****
Encryption	TLS
Port	587
Default Sender Address	testingthetestqa@gmail.com
Timeout (In Seconds)	60

A 'Check Configuration' button is located at the bottom right of the configuration section.

- 4) Click **Check Configuration**. If the entered configuration settings are correct, then a **SMTP Configured Successfully** banner is shown at the top of the portal.



Note

If you are configuring a Gmail account to set up SMTP in the Control Center, then you need to enable **Less Secure App Access** under the account settings in Google.

